LIGHTHAWK LED GEN II

FEATURES

Multi-Function switch
- Main light with high / low mode
- Rear signaling light
- Steady on / flashing modes

Battery Charge Indicator:
Red for charging / Green for fully charged

Low Battery Indicator: When 30 minutes of run time remain, high mode automatically switches to low mode and the front beam will begin to flash 3 times every 5 minutes.

SAFETY

UL PROTECTION METHODS	CLASS I, II, III DIV I GROUPS C-G, T1
UL 913 CSA 22.2 NO 157	CLASS I, II, III DIV II GROUPS A-G, T5
INTRINSICALLY SAFE	INGRESS PROTECTION LEVEL: IP67

FL1 STANDARDS

4-CELL LIGHTHAWK

225 LUMENS | 1M | 8H / 16H | 1M | 447 M | 70,000 CD

MODELS

#07612	4 CELL YELLOW LANTERN W/ 120V AC CHARGER
#07632	4 CELL YELLOW LANTERN W/ DC CHARGER
#07652	4 CELL YELLOW LANTERN W/ 220V AC CHARGER
#07672	4 CELL, YELLOW, DIRECT WIRE
#07612 UTIL	4 CELL, YELLOW 120V & DC
#07610	4 CELL ORANGE LANTERN W/ 120V AC CHARGER
#07630	4 CELL ORANGE LANTERN W/ DC CHARGER
#07650	4 CELL ORANGE LANTERN W/ 220V AC CHARGER
#07670	4 CELL, ORANGE, DIRECT WIRE
#07610 UTIL	4 CELL, ORANGE 120V & DC
#07611	4 CELL BLACK LANTERN W/ 120V AC CHARGER
#07631	4 CELL BLACK LANTERN W/ DC CHARGER
#07651	4 CELL BLACK LANTERN W/ 220V AC CHARGER
#07671	4 CELL, BLACK, DIRECT WIRE
#07611 UTIL	4 CELL, BLACK 120V & DC

ACCESSORIES

07690 Lighthawk Gen II Charger Base
07870 Lighthawk 12/24V DC Cord
20628 Lighthawk 120V AC Cord
20629 Lighthawk 220V Euro Cord
20627 Lighthawk 240V British Cord

MADE IN THE USA